

漏電遮断器 (1)

メーカー・形名	規	格	価格(台)	メーカー・形名	規	格	価格(台)			
[河村電器産業] (極・素子) (定格電圧) (定格電流)				[テンパール工業] (極素子) (定格電圧) (定格電流)						
過負荷・短絡保護用				経済形						
ZS	2P1E	100V	15A	4,290	GB-1ZA	2P1E 100V	15 ~ 30A	4,000		
"	2 1	"	20	4,290	" -2 "	2 2 100-100/200-200V	"	4,600		
"	2 1	"	30	4,290	" -2EA	2 2 "	"	4,800		
"	2 2	100/200V	20	4,290	" -3MEC	3 3 100-200V	1.3 ~ 30	8,880		
"	2 2	"	30	4,870	" -32EC	2 2 "	15 ~ 30	8,340		
ZL	2 2	100-200V	40	4,870	" -33 "	3 3 "	"	8,700		
"	2 2	"	50	10,800	" -52 "	2 2 "	15 ~ 50	10,400		
"	2 2	"	60	10,800	" -53 "	3 3 "	"	10,850		
"	2 2	"	75	10,800	" -62 "	2 2 "	60	11,300		
"	2 2	"	100	15,700	" -73 "	3 3 "	75	16,200		
ZR	2 2	"	125	15,700	" -102 "	2 2 "	50 ~ 100	20,000		
"	2 2	"	150	21,100	" -103 "	3 3 "	"	21,200		
ZL	3 3	"	30	27,600	" -122 "	2 2 "	60 ~ 125	22,300		
"	3 3	"	50	91,500	" -123 "	3 3 200-415V	"	23,500		
"	3 3	"	75	11,400	" -152 "	2 2 100-200	150	27,100		
"	3 3	"	100	16,800	" -153 "	3 3 200-415	"	28,700		
ZR	3 3	"	150	29,300	" -222EA	2 2 100-200	125 ~ 225	36,800		
単3 中性線欠相保護付				地絡保護専用						
ZSG	3P2E	"	20	9,440	" -223 "	3 3 200-415	"	38,400		
"	3 2	"	30	9,440	" -253 "	3 3 "	250	41,800		
[LS 産電] 過負荷・短絡保護用				" -403 "				3 3 "	250・300	84,300
経済形				" -603EB				3 3 "	可調整 (300 ~ 600)	197,300
EBE53c	3P	220/460V	5 ~ 50A	13,360	GT-2ZA	2P0E 100-200V	30A	3,400		
" 63c	3	"	60	15,120	" -2EA	2 0 "	"	3,650		
" 103c	3	"	60 ~ 100	21,360	" -31EA	3 0 "	"	5,200		
" 203c	3	"	125 ~ 225	40,320						
" 403c	3	"	250 ~ 400	109,440						
" 603c	3	"	500 ~ 600	240,552						
" 803c	3	"	700 ~ 800	291,920						
標準形										
EBS33c	3P	220/460V	5 ~ 30A	19,040						
" 53c	3	"	5 ~ 50	20,080						
" 63c	3	"	60	25,120						
" 103c	3	"	40 ~ 100	70,640						
" 203c	3	"	125 ~ 225	100,800						
" 403c	3	"	250 ~ 400	188,480						
" 603c	3	"	500 ~ 600	277,600						
" 803c	3P	"	700 ~ 800	409,600						
高遮断形										
EBH33c	3P	220/460V	5 ~ 30A	25,040						
" 53c	3	"	40 ~ 50	33,920						
" 103c	3	"	40 ~ 100	80,800						
" 203c	3	"	125 ~ 225	132,800						
" 403c	3	"	250 ~ 400	188,800						

漏電遮断器

制御機器



漏電遮断器 ZS 形



漏電遮断器 単3 中性線欠相保護付

河村電器産業製

I-V 特性測定装置 スtringトレサ



太陽光発電システムの異常Stringを特定可能!



特長

- ① 最大4 String分の測定結果を同一画面に表示できるため、良否判定が容易。
- ② 同時測定機能により、瞬間的な天候の変化にも影響を受けず、同一条件での測定可能。

Togami 株式会社 戸上電機製作所 佐賀市大財北町 1-1 お客様サービスセンター ☎ 0120-25-7867

カタログ請求番号 1543

(カタログ請求の方法については巻末1ページをご覧ください)